



SHMOO



TECH SPECS

westomatic
make it happen

OPTIONS

AUDIT CAPABILITY	USB Wireless	Standard Optional
FLAVOUR CAPACITY	1 x Double Canister (4kg) 3 x Single Canister (1.5kg)	Standard Standard
CHILLER	Flash Cooler	Standard
BOTTLE SENSOR		Standard
DISPLAY	4-line LCD Display 12" Media Screen	Standard Standard
GRAPHICS	SHMOO – Black or White	Standard
LOCK	New T bar 3-point lock	Standard
PAYMENT SYSTEM	Freevend Cashless Payment System	Standard Optional
WATER FILTER	FLUXX FX Dual Filter	Standard
UV TREATMENT	UV Filter	Standard
PUMP & TANK KIT		Optional

TECHNICAL SPECIFICATIONS

IDLE PHASE (Watt / hr)	41.39
DISPENSE PHASE (Watt / hr)	140
PER LITRE (watts / hr / litre)	30.43
PRESSURE	138 kpa (1.37 Bar) min 828 kpa (8.27 Bar) max
SUPPLY	15mm BSP from rising main
DIMENSIONS	W 500mm x H 1825mm x D 670mm
WEIGHT (kg)	101
VOLTAGE (volts)	230-240
CURRENT (amps)	12
FREQUENCY (hz)	50

WATER QUALITY

	Tap Water	Bottled Water	Mains fed Water Cooler	Carbon Water Filter	RO Water	Westomatic Water
Chlorine	✗	✓	✗	✓	✓	✓
Improved Taste & Odour	✓	✓	✓	✓	✓	✓
Dirt	✓	✓	✓	✓	✓	✓
Sediment	✓	✓	✓	✓	✓	✓
Rust	✗	✓	✗	✓	✓	✓
Parasites	✓	✓	✓	✓	✓	✓
Heavy Metals	✗	✓	✗	✓	✓	✓
Arsenic	✗	✓	✗	✓	✓	✓
Volatile Organic Compounds	✓	✓	✓	✓	✓	✓
Micro Plastics	✗	✗	✗	✗	✗	✓
Algae	✗	✗	✗	✗	✗	✓
THM	✗	✗	✗	✗	✓	✓
TDS	✗	✗	✗	✗	✓	✓
Herbicides	✗	✓	✗	✗	✓	✓
Pesticides	✗	✓	✗	✗	✓	✓
UV Filtration	✗	✗	✗	✗	✗	✓